

# KLMA-LSZH

75 V



<b>CONDUCTOR</b>	Solid copper conductor
<b>INSULATION</b>	PE
<b>STRANDING</b>	Conductors twisted together Solid tinned copper drain wire under screen
<b>SCREEN</b>	Aluminium polyester tape
<b>SHEATH</b>	LSZH Thermoplastic Standard colour light grey
<b>REFERENCE STANDARD</b>	EN 50288-7, SFS 2755

## APPLICATION

Cable for instrumentation, alarm systems and personal call finders. For fixed installation.

## PHYSICAL PROPERTIES:

<b>MIN. BENDING RADIUS (installation/fixed)</b>	15 x Ø/10 x Ø
<b>CORE IDENTIFICATION</b>	1. Blue 2. Yellow 3. White 4. Red

## MAIN CHARACTERISTICS:

<b>FIRE PERFORMANCE</b>	Cca, s2, d1, a1 IEC 60332-1-2
<b>RATED VOLTAGE</b>	75 V
<b>MIN. INSTALLATION TEMPERATURE</b>	-5 °C
<b>OPERATING TEMPERATURE</b>	-5 - 70 °C

## KLMA-LSZH

Part number	No. of conductors x Conductor Ø	Nominal outer Ø mm	Weight kg/km	Standard length m	
3450225020	2 x 0.8 + 0.8	3.9 ± 0.3	25	150	coil
3452225020	2 x 0.8 + 0.8	3.9 ± 0.3	25	600	drum
3450225040	4 x 0.8 + 0.8	4.5 ± 0.3	37	150	coil
3452225040	4 x 0.8 + 0.8	4.5 ± 0.3	37	600	drum